



Dart Aerospace Ltd.
1270 Aberdeen St
Hawkesbury, ON
K6A 1K7
Canada

Tel (613) 632-5200

D350-636-012
Job Sheet 171305



Part No: D350-636-012

Job Qty: 1 ea

Part Name: Skidtube RH, Std Wearplates, DART (Apical) Cylindrical/Aerazur Float Comp.



Part Weight: 0 lbs

Status: Scheduled

Priority: Medium

Job Created: 1/30/18

Job Tracking No:

Due Date: 2/9/18

Created By: Michelle Gagnon-Donovan

Type: SOLD

Description:

Note: DWG D3492 REV E SHEET 1, D2750-042 REV G SHEETS 1,2,5,9 IPP Rev:I 02.09.25 IPP Rev:J 06-03-23 As per Rev D IPP Rev:K 06-07.13 As per dsi9343 IPP Rev:L 07-07-28 Added SS Wearplates(Rev E) JLM Verf:EC IPP Rev:M 08-04-22 DD verified:EC IPP Rev:N 08-09-23 revF DD verified:ec IPP Rev:O 09-02-06 per PAR09-010 DD verf:EC IPP Rev:P 10.06.22 revise seq110 DD verf:EC IPP Rev:Q 10.10.01 as per IIN revH DDverf:EC IPP REV:R 13.08.27 PER ECN13-594 DD VERF:JLM

Ship Via:

Bill of Materials

DART
AEROSPACE
S040932



Skidtube RH, Std Wearplates, DART (Apical)
Cylindrical/Aerazur Float Comp.

PART NO: D350-636-012

Original Serial #: S040932

Revision:

Operation:

Change No:

Start up Operation 02/09/18
CHG007

Job No: 171305

Dart Aerospace Ltd.

1270 Aberdeen Street
Hawkesbury, ON K6A 1K7
CANADA

TEL.: 1 613 632-5200

Email: sales@dartaero.com

www.dartaerospace.com

Job Routing									
Op No	Operation	Qty	Start Date	Due Date	Standard		Workcenter/Supplier		Sign-off
					Setup hrs	Run Hrs	Workcenter / Supplier	Lead Time	
90	Start up Operation	1 Ea		2/8/18	0.00	0.00	Start Up Skidtubes-1		
110	Skidtubes	1 pcs		2/8/18	0.00	4.36	Skidtubes-4		BAS
120	QC	1 pcs		2/8/18	0.00	0.00	QC10		38 DAS
130	QC	1 pcs		2/8/18	0.00	0.00	QC5		9-89 38
140	HandFinish	1 pcs		2/8/18	0.00	0.91	HandFinish1		18-02-19-09
150	QC	1 pcs		2/8/18	0.00	0.00	QC7-2		BE
160	Skidtubes	1 pcs		2/8/18	0.00	4.36	Skidtubes-1		BE
170	QC	1 pcs		2/8/18	0.00	0.00	QC10		DD 18-02-27
180	QC	1 pcs		2/8/18	0.00	0.00	QC5		PD 18-02-27
190	HandFinish	1 pcs		2/8/18	0.00	0.91	HandFinish2		18-02-27
200	SprayPaint	1 pcs		2/8/18	0.00	0.69	Spray Paint		18-02-27
210	QC	1 pcs		2/8/18	0.00	0.00	QC14		18-02-28
230	HandFinish	1 pcs		2/9/18	0.00	0.91	HandFinish4		18-03-01
240	QC	1 pcs		2/9/18	0.00	0.00	QC5		18-3-1-2K
250	Packaging	1 pcs		2/9/18	0.00	0.00	Packaging1-3		MAR 02 2018
260	QC	1 pcs		2/9/18	0.00	0.00	QC4		18-3-6
265	DC	1 pcs		2/9/18	0.00	0.00	DC		18-3-6
270	Packaging	1 pcs		2/9/18	0.00	0.00	Packaging3-1		18-3-6
280	QC21-FG	1 Ea		2/9/18	0.00	0.00	QC21		18-3-6

Part Op 110 - 1- Pick D2600-3 Bent Drill pilot holes as per Dwg D2750 sheet 4 (D2750-2 details). Drill using drill Jig DT8150 & Descriptions: DT8863A for second side only DT8863B for first side (detail K) 4- Locate DT8329 off of blade fitting bolt holes and drill pilot holes for blade fitting. Open to 0.500" using hole saw. VERIFY AND RECORD FWD BEND ANGLE. 6- Drill pilot holes for wearplates as per Dwg D2750 using DT8108 open to 0.297". 7- Open up holes of Detail J to 0.297" (total of 2 holes per side) 8- Weld D2744 Cap as per Dwg D2750 and QSI 004. Fill grooves in bend left from bending as per QSI 004 9- Grind welds flush as per Dwg D2750

160 - 1- Open up holes of Detail L using hole saw and ground handling to 0.625" (total of 8 holes per side) as per dwg D2750. 2- Open up holes of Detail K using hole saw to 0.750" (total of 4 holes per side) as per dwg D2750. 3- Open float holes using uni-bit to .500" (4 per Side) 4- Chamfer holes of Detail K, L, ground handling and float holes per dwg D2750 (welding instructions on sheet 9) 5- Deburr and blow out all chips from inside of tube 6- Prepare tube for welding, remove alodine as required. 7- Bond web D2739 in place as per QSI 015, let cure for 12hrs. A/R Sikaflex-291 batch: M1386124 exp. date: 2018-04-21 **ATTN: USE I-BEAM LOCATION AID (BLADE FITTING)** 8- Weld spacers D3490-1, D3490-3 and D2743 as per dwg D2750 & QSI004 (welding instructions on sheet 9) A/R Aluminum Rod batch: 9- At section AP-AP drill out x-bolt spacer to 0.404" 10-Grind welds flush as per Dwg D2750 11- Spot face ground handling holes section (total of 4 places per side) as per dwg D2750 12- Deburr holes, ensure tube is free of all scratches before sending to paint.

180 - ***VERIFY C'BOARD IS GOOD***

190 - Re-alodine tube as per QSI 005 section 4.1.2.1 do not acid etch.

200 - 1- PRIME AS PER DWG AND QSI 005 4.2 PRIMER PRC DESOTO 515X349 BATCH: 137670 2- PAINT WHITE AS PER DWG AND QSI 005 4.2 PAINT BATCH: 138741

210 - Inspect for foreign object per QSI 024

230 - 1-Install inserts as per dwg D2750 2-Inspect for Foreign Objects 3-Install blade fitting D3488-042, wearshoes and ground handling hardware as per dwg D2750 SIKA FLEX 241 BATCH: M1386124 EXP DATE: 18/04 4- assemble o-ring to plug as per dwg D3492 and apply o-ring lube A/R 55-o-ring lube batch: 1155977 5-Coat all exposed fasteners with "LPS Procyon" batch: M133690

265 - record fwd angle: 89.9° Photocopy blue file and type labels per PPP D350-636-012 CHG 007

270 - Package as per PPP D350-636-012

Job BOM

Part / Item	Component Name	Quantity	Operation	Container
D2600-3-BENT-RH	Extrusion Bent RH	1 Ea (1 ea)	90-Start up Operation	5030354
D2744	Cap	1 Ea (1 ea)	90-Start up Operation	5038885
D2739	350 I-Beam	1 Ea (1 ea)	160-Skiddtubes	5040307
D2743	Crossbolt Spacer	8 Ea (8 ea)	160-Skiddtubes	5026388
D3490-1	Cross Bolt Spacer	4 Ea (4 ea)	160-Skiddtubes	5017322
D3490-3	Cross Bolt Spacer	4 Ea (4 ea)	160-Skiddtubes	5030890
ALS4-1032-225	Rivnut	38 Ea (38 ea)	230-HandFinish	
AN3C5A	Bolt	34 Ea (34 ea)	230-HandFinish	
AN3C6A	Bolt	4 Ea (4 ea)	230-HandFinish	
AN6C44A	Bolt	4 Ea (4 ea)	230-HandFinish	
AN8C35A	Bolt	1 Ea (1 ea)	230-HandFinish	
D2745	Bushing	8 Ea (8 ea)	230-HandFinish	
D3488-042	Blade Fitting RH	1 Ea (1 ea)	230-HandFinish	
D3492-1	Plug	8 Ea (8 ea)	230-HandFinish	
D3492-3	Plug	8 Ea (8 ea)	230-HandFinish	
D3535-25	Wearplate Center	1 Ea (1 ea)	230-HandFinish	
D3536-25	Gasket Center	1 Ea (1 ea)	230-HandFinish	
D3537-1	Wearpad	3 Ea (3 ea)	230-HandFinish	
D3631-1	Washer	8 Ea (8 ea)	230-HandFinish	
D3791-1	Wearpad	1 Ea (1 ea)	230-HandFinish	
D3793-1	Wearplate Fwd	1 Ea (1 ea)	230-HandFinish	
D3793-3	Wearplate Aft	1 Ea (1 ea)	230-HandFinish	
D3794-1	Gasket Fwd	1 Ea (1 ea)	230-HandFinish	
D3794-3	Gasket Aft	1 Ea (1 ea)	230-HandFinish	
MS21043-6	Nut	4 Ea (4 ea)	230-HandFinish	
MS21083C8	Nut	1 Ea (1 ea)	230-HandFinish	
NAS1149C0332R	Washer	38 Ea (38 ea)	230-HandFinish	
NAS1149C0832R	Washer	1 Ea (1 ea)	230-HandFinish	
NAS1515H3L	Washer	4 Ea (4 ea)	230-HandFinish	
NAS1611-010	O-Ring	8 Ea (8 ea)	230-HandFinish	
NAS1611-013	O-Ring	8 Ea (8 ea)	230-HandFinish	
AN8C21A	Bolt	2 Ea (2 ea)	250-Packaging	504137162
D2741	Replacement Blade	1 Ea (1 ea)	250-Packaging	5063200-1
D3493-1	Washer	2 Ea (2 ea)	250-Packaging	5031096
D3532-1	Spacer	2 Ea (2 ea)	250-Packaging	5026739
MS21083C8	Nut	2 Ea (2 ea)	250-Packaging	5016888
NAS1149D0863J	Washer	2 Ea (2 ea)	250-Packaging	5125268

Job Allocations				
Operation	Component Part	Required	Inventory	Allocated
90-Start up Operation	D2600-3-BENT-RH	1	1	0
	D2744	1	2	0
160-Skidtubes	D2739	1	8	0
	D2743	8	159	0
	D3490-1	4	48	0
	D3490-3	4	31	0
230-HandFinish	ALS4-1032-225 <i>5007280</i>	38	1,749	0
	AN3C5A <i>5019396</i>	34	1,069	0
	AN3C6A <i>5019397</i>	4	222	0
	AN6C44A <i>FM137055-1</i>	4	487	0
	AN8C35A <i>FM137203</i>	1	83	0
	D2745 <i>5026736</i>	8	185	0
	D3488-042 <i>F163247-2</i>	1	14	0
	D3492-1 <i>5025647</i>	8	179	0
	D3492-3 <i>5026057x4</i>	8	232	0
	D3535-25 <i>5040748</i>	1	20	0
	- D3536-25 <i>5046424</i>	1	23	0
	D3537-1 <i>5037413</i>	3	18	0
	D3631-1 <i>5008168</i>	8	134	0
	D3791-1 <i>F161928</i>	1	18	0
	D3793-1 <i>5038363</i>	1	19	0
	D3793-3 <i>50382647</i>	1	25	0
	D3794-1 <i>5031919</i>	1	27	0
	- D3794-3 <i>5046244</i>	1	17	0
	MS21043-6 <i>5041601</i>	4	67	0
	MS21083C8 <i>5034401</i>	1	123	0
	NAS1149C0332R <i>501938</i>	38	3,099	0
	NAS1149C0832R <i>M138409-121</i>	1	108	0
	NAS1515H3L <i>FM137361-25</i>	4	435	0
	NAS1611-010 <i>5022098</i>	8	359	0
	NAS1611-013 <i>5022099</i>	8	447	0
250-Packaging	AN8C21A	2	209	0
	D2741	1	33	0
	D3493-1	2	62	0
	D3532-1	2	32	0
	MS21083C8	2	123	0
	NAS1149D0863J	2	189	0
Part Specifications				
Specifications could not be found.				

Plex 1/30/18 3:29 PM Dart.Gagnon.Michelle

001277
 001324

QTY -041	QTY -042	QTY -043	QTY -044	PART NUMBER	DESCRIPTION
X				D2750-041	350 SKIDTUBE ASSEMBLY, LH
	X			D2750-042	350 SKIDTUBE ASSEMBLY, RH
		X		D2750-043	350 SKIDTUBE ASSEMBLY, LH
			X	D2750-044	350 SKIDTUBE ASSEMBLY, RH
1	1	1	1	D2739	WEB
8	8	8	8	D2743	SPACER
1	1	1	1	D2744	CAP
8	8	8	8	D2745	BUSHING
1				D2750-1	SKIDTUBE WELDMENT, LH
	1			D2750-2	SKIDTUBE WELDMENT, RH
		1		D2750-3	SKIDTUBE WELDMENT, LH
			1	D2750-4	SKIDTUBE WELDMENT, RH
1		1		D3488-041	BLADE FITTING, LH
	1		1	D3488-042	BLADE FITTING, RH
4	4	4	4	D3490-1	SPACER
4	4			D3490-3	SPACER
		4	4	D3490-5	SPACER
8	8	8	8	D3492-041	PLUG ASSEMBLY
8	8			D3492-043	PLUG ASSEMBLY
		8	8	D3492-045	PLUG ASSEMBLY
1	1	1	1	D3535-25	WEARSHOE
1	1	1	1	D3536-25	GASKET
3	3	3	3	D3537-1	WEARPAD
8	8	8	8	D3631-1	WASHER
1	1	1	1	D3791-1	WEARPLATE
1	1	1	1	D3793-1	WEARSHOE
1	1	1	1	D3793-3	WEARSHOE
1	1	1	1	D3794-1	GASKET
1	1	1	1	D3794-3	GASKET
38	38	38	38	ALS4-1032-225	INSERT (OR ALS7-1032-225, AKS4-1032-225, AELS-1032-225)
34	34	34	34	AN3C5A	BOLT
4	4	4	4	AN3C8A	BOLT
4	4	4	4	AN8C44A	BOLT
1	1	1	1	AN8C35A	BOLT
38	38	38	38	AN960C10L	WASHER
1	1	1	1	AN960C816L	WASHER
4	4	4	4	MS21043-6	NUT
1	1	1	1	MS21083C8	NUT
4	4	4	4	NAS1515H3L	WASHER

GENERAL NOTES:

- MATERIAL: MAKE D2750-1/-2/-3/-4 FROM D2600-3 EXTRUSION (INITIAL LENGTH = 120.0).
- FINISH: ACID ETCH, ALODINE ASSEMBLY PER DART QSI 005 4.1 PRIOR TO INSTALLING D2739 WEB.
 STANDARD: PRIME (REF. 4.2.1.3.3) AND PAINT WHITE PER DART QSI 005 4.2
 OPTIONAL: POWDER COAT WHITE (REF. 4.3.5.1) PER DART QSI 005 4.3
 BLACK ANTI-SKID PAINT AS INDICATED TO 1.0 ABOVE SKIDTUBE CENTER-LINE PER DART 005 4.4 (OPTIONAL).
- TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- UNITS: INCHES UNLESS OTHERWISE NOTED
- BREAK SHARP EDGES: N/A
- IDENTIFICATION: N/A
- WEIGHT: D2750-041/-042/-043/-044 = 26.5 LBS
- WELD PER DART QSI 004
- INSTALL ALS4-1032-225 INSERTS AFTER FINISH AS INDICATED. DRILL 'F' SIZE HOLES ($\phi 0.297$) FOR WEARSHOE INSERTS
- FINAL CONFIGURATION SHOULD HAVE THE FOLLOWING MINIMUM MECHANICAL PROPERTIES:
 MINIMUM YIELD TENSILE STRENGTH = 35 KSI
 MINIMUM ULTIMATE TENSILE STRENGTH = 38 KSI
- COAT ALL EXPOSED FASTENERS WITH LPS LABORATORIES "LPS PROCYON" AFTER FINAL ASSEMBLY, CLEAN EXCESS OFF
- SPACER AND PLUG INSTALLED SAME AS SECTION AJ-AJ EXCEPT HORIZONTAL
- SPACER AND PLUG INSTALLED SAME AS SECTION AP-AP EXCEPT HORIZONTAL

SHOP COPY
 RETURN TO
 ENGINEERING
 UNCONTROLLED COPY
 SUBJECT TO AMENDMENT
 WITHOUT NOTICE
 WORK ORDER
 NO. 171305

JAN 30 2018

RELEASED
 2013-08-13

G	CORRECTED TOLERANCE ON $\phi 0.500$ THRU HOLE: IS $+0.010/-0.000$, WAS $+0.100/-0.000$ (ZN B3-4, B2-5); ADD VIEW TO CONTROL FWD BEND ORIENTATION (ZN D-1-4/-5/-6/-7); UPDATED FINISH OPTIONS: INSIDE OF TUBE NO LONGER SPRAYED WITH LPS-3. REASON: PART13-276 AND NCR13-2757	MB	13.07.11
F	INCORPORATE DSI 9413: QTY (3) D3537-1 WAS QTY (5) (ZN C8-1); D3791-1/3 REPLACES D3535-1/3-35 (ZN C8-1); D3794-1/3 REPLACES D3536-1/3-35 (ZN B8-1); ADD D3791-1 (ZN C8-1); WEARSHOE HOLES UNDER FWD/AST SADDLE REMOVED (8 PL) WEARSHOE HARDWARE QTY UPDATED (ZN B8-1); D3488-041/-042 HARDWARE UPDATED (ZN C1-8, 9, 10, 11); ADD NOTE 12 AND 13 (ZN A6-1); REASON: REF. NCR 06-043	PH	08.07.16
E	CHANGE TO STAINLESS STEEL WEARPLATES; ADD RUBBER GASKETS; CHANGE INSERTS: ADD D3631-1; REMOVE QTY (38) NAS1515H3L; REMOVE QTY (10) NAS1515H8L; REMOVE D2741, QTY (2) AN960C816; REMOVE QTY (2) MS21083C8	CB	07.05.17
D	ADD HOLES AND SPACERS FOR APICAL FLOATS; INCORPORATE DEO 9133/8157	PH	06.01.05
C	ADD D2750-3/D2750-4; INCORPORATE D2738 AND D2740	CP	06.11.18
B	CHANGE MS24694-S293 TO AN8-16A	CP	06.09.01
A	NEW ISSUE	DS	06.04.16
REV.	DESCRIPTION	BY	DATE
DESIGN	MM		
DRAWN			
CHECKED			
MFG. APPR.			
APPROVED			
DE APPR.			
DATE	13.07.11		

DART AEROSPACE USA, INC.

KENT, WA

DRAWING NO.

D2750

TITLE

350 SKIDTUBE ASSEMBLY

COPYRIGHT © 1999 BY DART AEROSPACE USA, INC.

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL. IT IS NOT TO BE USED FOR ANY PURPOSES OR COPIED OR REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT THE WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.


REV. G

SHEET 1 OF 11


SCALE

NTS

SHOP COPY
 RETURN TO
 ENGINEERING
 UNCONTROLLED COPY
 SUBJECT TO AMENDMENT
 WITHOUT NOTICE
 WORK ORDER
 NO. 171305 *mg*
 JAN 30 2018



D2750-041 350 SKIDTUBE ASSEMBLY, LH



D2750-042 350 SKIDTUBE ASSEMBLY, RH

RELEASED
 2013-08-13
MP


DESIGN	MM	DART AEROSPACE USA, INC.	
DRAWN	<i>[Signature]</i>	KENT, WA	
CHECKED	<i>[Signature]</i>	DRAWING NO. D2750	REV. G
MFG. APPR.	<i>[Signature]</i>	SHEET 2 OF 11	
APPROVED	<i>[Signature]</i>	TITLE	SCALE
DE APPR.	<i>[Signature]</i>	350 SKIDTUBE ASSEMBLY	NTS
DATE	13.07.11	COPYRIGHT © 1998 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PROVIDED CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS UNDERSTANDING THAT IT IS NOT TO BE USED FOR ANY PURPOSES OR REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS WITHOUT THE WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	

WITHOUT NOTICE
WORK ORDER
NO. 171305

**WITHOUT NOTICE
WORK ORDER**


NO. 171305

JAN 30 2018




OUTBD


**MAX ALLOWABLE
TWIST ON FWD BEND
(VIEWED LOOKING FWD)**




D2750-2 RH SKIDTUBE




DETAIL J
SCALE 2X




DETAIL K ^{C7-5}
SCALE 2X




DETAIL L
SCALE 2X




DETAIL M
SCALE 2X




SECTION N-N
SCALE 3X, 2 PL



SECTION P-P
SCALE 3X, 17 PL



SECTION Q-Q
SCALE 3X 4 PL



SECTION R-R
SCALE 3X 4 PL

DESIGN	MM	DART AEROSPACE USA, INC.	
DRAWN		KENT, WA	REV. G
CHECKED		DRAWING NO.	SHEET 8 OF 1
MFG. APPR.		D2750	SCALE
APPROVED		TITLE	NTS
DE APPR.		350 SKIDTUBE ASSEMBLY	
DATE	13.07.11	COPYRIGHT © 1999 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PLACED UNDER THE PROVISIONS OF THE PATENT AND TRADE SECRET ACTS OF 1952 AND 1956. IT IS NOT TO BE USED FOR ANY PURPOSE OR IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF DART AEROSPACE USA, INC.	







SHOP COPY
RETURN TO
ENGINEERING
UNCONTROLLED COPY
SUBJECT TO AMENDMENT

WITHOUT NOTICE
WORK ORDER
NO. 171305

JAN 30 2018

RELEASED
2013-08-13

D2750-042 350 SKIDTUBE ASSEMBLY, RH



DESIGN	MM	DART AEROSPACE USA, INC.
DRAWN		KENT, WA
CHECKED		DRAWING NO. D2750
MFG. APPR.		REV. G
APPROVED		SHEET 9 OF 11
DE APPR.		TITLE
DATE	13.07.11	350 SKIDTUBE ASSEMBLY
		SCALE
		NTB

COPYRIGHT © 1999 BY DART AEROSPACE USA, INC.
THIS DOCUMENT IS PROVIDED AS INFORMATION AND IS NOT TO BE USED FOR ANY PURPOSES OTHER THAN THAT FOR WHICH IT WAS PROVIDED WITHOUT THE WRITTEN PERMISSION OF DART AEROSPACE USA, INC.



Dart Aerospace Ltd.
1270 Aberdeen St
Hawkesbury, ON
K6A 1K7
Canada

Tel (613) 632-5200

Container View (Active) - Master Unit Containers

Master Unit No	Container No	Part No	Part Name	From Container	Current Location	Quantity
001324	S047162	AN8C21A	Bolt	FM137162	OVER004	2
001324	S047164	D2741	Replacement Blade	F163260-1	ST538	1
001324	S047152	D3493-1	Washer	s031096	ST037	2
001324	S047136	D3532-1	Spacer	s026734	ST038	2
001324	S047135	MS21083C8	Nut	S016888	ST297	1
001324	S047134	NAS1149D0863J	Washer	F125268	ST263	2

Note: Ad hoc query view of Part.dbo.Container where Container.Active = 1.

Plex 3/2/18 8:29 AM Dart.joly.jocelyne

PAGE 1 OF 1

Description: SKIDTUBE STD LH/RH, FLOAT COMPATIBLE

[illegible]